

Transmittance **$U_w \geq 0.71$ (W/m²K)**

Consult typology, dimensions and glass.

Acoustic insulation

Maximum glazing	73 mm
Minimum glazing	16 mm
Maximum acoustic insulation	Rw = 46 dB

Sightlines

Frame	80 mm
Sash	88 mm

Profile Thickness

Window	1.5 mm
--------	--------

Polyamide strip length 45 mm**Maximum dimensions / Sash**

Width (L) = 1,500 mm

Height (H) = 2,600 mm

Consult maximum weight and dimensions according to typologies.

Maximum weight / Sash 160 kg**Certificates**

ATG Certification - 3235



SKG Certification

**Categories achieved at test centre**

Protection against atmospheric agents.

Air permeability**(UNE-EN 12207):** Class 4**Water tightness****(UNE-EN 12208):** Class E1950**Wind resistance****(UNE-EN 12210):** Class C5

* Reference test 1.23 x 1.48 m / 2 sashes.

Burglar resistance**(UNE-EN 1627):** Grade RC2 (WK2)

Test verified by

ALUMINIOS CORTIZO S.A.U.**Extrusion alloy**

6063 T-5

Finishes

Possibility of dual colour

Colour powder coating (RAL, mottled & rough)

According to Qualicoat >60 microns

Wood effect powder coating

According to Qualideco standard

Anodised

According to Ewwa Euras / Standard Class 15 / Optionally Class 20 and 25

Opening possibilities

Inward opening: side hung, tilt & turn, parallel sliding and bottom hung.

Outward opening: side hung and top hung.

